HERCULES HOISTS LIMITED.

2005. HERCULES HOISTS LIMITED. All Rights Reserved

Chain Pulley Block

INDEF M 6T/20T COMPACT BLOCKS



HHL introduces its customers to Indef M 6T / 20T Compact Blocks providing you features that are light weight & Sturdy making it very easy to handle

Lifelong Lubrication enhances efficiency of performance with minimal maintenance required.

Consists of Surface hardened Gears for an extended working life

Uses needle roller bearings delivering a higher operating efficiency

Ensuring Smooth passage of load chain with Machined guide rollers

A Unique cover design that smoothens hand chain operation

Self sustaining maintenance free friction brake in turn reducing downtime Equipped with a Grade 80 Load Chain for strength & wear resistance also a longer chain life Elegantly modeled with an Anticorrosive powder coated finish and has better aesthetics Compact Design & Low Headroom and Light Weight

Fig. 1 H	Fig. 4	TUPPERHOOK & LOWER FIDED	Fig. 7	Fig.	9.10		
Fig. 2			Fig. 8	Fig.	Fig. 11		
Fig. 3	н Э		Fig. 9 H		Fig. 12		
Capacity	No. of Falls	For each hand chain. Hand chain required to be passed over for lifting load through one metremetres (approx)	Running Pull On Each Hand Chain	Hook Opening	ing Weight For 1 M Addl. Lift (approx)		
16 T	6	468	45 kg.	95 mm	14.5kg.		
20 T	6.	624	46 x 2 kg.	95 mm	20.2 kg.		

COMBINATIONS	Fig.		I6 TONNE		Weight	20 TONNE		Weight		
	16 T	20 T	Length mm	Width mm	Head room 'H' mm	For 3 M Lift (kg.) (approx.)	Length mm	Width mm	Head room 'H' mm	For 3 M Lift (kg.) (approx.)
Upper Fixed eye suspension and lower fixed	1	7	670	220	640	138	1175	220	640	200
Upper & Lower Swivelling Hook	2	8	670	220	1175	218	1175	220	1175	280
Upper Fixed eye suspension and lower Swivelling Hook	3	9	670	220	985	178	1175	220	985	240
Upper Swivelling Hook and lower fixed	4	10	670	220	700	178	1175	220	700	240
Trolley Suspension and lower fixed	5	11	1300	*F+360	795	440	1300	*F+360	795	500
Trolley Suspension and lower Swivelling Hook	6	12	1300	*F+360	1140	470	1300	*F+360	1140	540

*F=Flange Width of 'l' Beam (Data tolerance +/_ 10%)

Manufactured & Marketed by HERCULES HOISTS LIMITED.



Marketed in India by HERCULES HOSITS LIMITED 110, Minerva Industrial Estate, Mulund West, Mumbai - 400080 INDIA. Tel :- 91-22-25624214 , 91-22-25680381 Fax :- 91-22-25683933 , 91-22-25624215 Email - enquire@indef.com Website - www.indef.com

Manufactured by : Hercules Hoists Ltd.

